| REL FOR ASM | QTY | TECHNICAL APPROVAL | | | DATE | EC NO. | | DATE | EC NO. | PART NO. 3046291 |
|---|---|---|---|---|---|---|---|---|---|---|
| | | ELECTRICAL | | | 17SEP08 | REV 001 | | | | |
| | | MATERIAL | | | | | | | | DEVELOPMENT NO. Q/M |
| | | MFG | | | | | | | | |

NOTES:

(1) THIS PART MUST COMPLY WITH ALL REQUIREMENTS OF THE LAWS BASED ON THE CONEG MODEL LEGISLATION IN THE U.S. AND THE CURRENT EUROPEAN UNION'S DIRECTIVE CONCERNING PACKAGING. IT MUST NOT BE COMPRISED OF, OR PRODUCED USING, OZONE-DEPLETING SUBSTANCES. NO CONCENTRATION OF LEAD, CADMIUM, MERCURY, HEXAVALENT CHROME, IS PERMITTED WHEN PURPOSELY ADDED AND THE SUM OF THE CONCENTRATION OF ALL FOUR METALS SHALL NOT EXCEED 100 PPM AS CONTAMINANTS. NOXIOUS CONSTITUENTS SHALL BE MINIMIZED AND ALL PACKAGING SHALL BE MANUFACTURED TO MINIMIZE THE ENVIRONMENTAL IMPACT AS DESCRIBED IN THE "LEXMARK SUPPLIER AND INTERPLANT PACKAGING AND HANDLING SPECIFICATION".

THIS DRAWING REPRESENTS A ROLL OF FILAMENT REINFORCED PRESSURE SENSITIVE TAPE
THE TAPE MUST BE 3M 8915
WIDTH = 18mm
ROLL LENGTH = 55 METERS

3046291

| | | | | | |
|---|---|---|---|---|---|
| MATERIAL NO. | | MUST CONFORM TO ENG SPEC: 1041400 | | SCALE: 1:1 | PART NO. 3046291 |
| MATL ALTERNATE NO. | | TOLERANCES UNLESS NOTED | | THIRD ANGLE PROJECTION | TITLE TAPE |
| | | LINEAR ± | | | 3M 8915 FILAMENT TAPE |
| CASE DEPTH | | ANGLES ± | | | DESIGNER TRG 18SEP08 |
| HARDNESS | | RADII UNLESS NOTED | | | CHECKED TRG 18SEP08 |
| SURFACE TREATMENT | CODE NO. | EDGE/CORNER BREAKS | OUTSIDE MAX | | APPROVED GKK 18SEP08 |
| | | | INSIDE MAX | | CLASS GKK 18SEP08 |

SI metric A0

THIS DOCUMENT IS THE PROPERTY OF LEXMARK. ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO A REQUEST FOR QUOTATION OR FOR THE PERFORMANCE OF WORK FOR LEXMARK. ALL QUESTIONS MUST BE REFERRED TO THE LEXMARK PURCHASING DEPARTMENT. ALL REFERENCES TO IBM OR LII IN THIS DOCUMENT SHOULD BE REPLACED WITH LEXMARK.

LEXMARK I-DEAS