REL FOR ASM	QTY	TECHNICAL APPROVAL			DATE	EC NO.		DATE	EC NO.	PART NO. 3046291
		ELECTRICAL			17SEP08	REV 001				
		MATERIAL								DEVELOPMENT NO. Q/M
		MFG								

NOTES:

(1) THIS PART MUST COMPLY WITH ALL REQUIREMENTS OF THE LAWS BASED ON THE CONEG MODEL LEGISLATION IN THE U.S. AND THE CURRENT EUROPEAN UNION'S DIRECTIVE CONCERNING PACKAGING. IT MUST NOT BE COMPRISED OF, OR PRODUCED USING, OZONE-DEPLETING SUBSTANCES. NO CONCENTRATION OF LEAD, CADMIUM, MERCURY, HEXAVALENT CHROME, IS PERMITTED WHEN PURPOSELY ADDED AND THE SUM OF THE CONCENTRATION OF ALL FOUR METALS SHALL NOT EXCEED 100 PPM AS CONTAMINANTS. NOXIOUS CONSTITUENTS SHALL BE MINIMIZED AND ALL PACKAGING SHALL BE MANUFACTURED TO MINIMIZE THE ENVIRONMENTAL IMPACT AS DESCRIBED IN THE "LEXMARK SUPPLIER AND INTERPLANT PACKAGING AND HANDLING SPECIFICATION".

THIS DRAWING REPRESENTS A ROLL OF FILAMENT REINFORCED PRESSURE SENSITIVE TAPE
THE TAPE MUST BE 3M 8915
WIDTH = 18mm
ROLL LENGTH = 55 METERS

MATERIAL NO.		MUST CONFORM TO ENG SPEC: 1041400		SCALE: 1:1	PART NO. 3046291
MATL ALTERNATE NO.		TOLERANCES UNLESS NOTED		SI metric A0	TITLE TAPE
		LINEAR ±		0 25 (MM) (INCH)	3M 8915 FILAMENT TAPE
CASE DEPTH		ANGLES ±		THIRD ANGLE PROJECTION	DESIGNER TRG 18SEP08
HARDNESS		RADII UNLESS NOTED			CHECKED TRG 18SEP08
SURFACE TREATMENT	CODE NO.	EDGE/CORNER BREAKS	OUTSIDE MAX		APPROVED GKK 18SEP08
			INSIDE MAX		CLASS GKK 18SEP08

THIS DOCUMENT IS THE PROPERTY OF LEXMARK. ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO A REQUEST FOR QUOTATION OR FOR THE PERFORMANCE OF WORK FOR LEXMARK. ALL QUESTIONS MUST BE REFERRED TO THE LEXMARK PURCHASING DEPARTMENT. ALL REFERENCES TO IBM OR LII IN THIS DOCUMENT SHOULD BE REPLACED WITH LEXMARK.

3046291

LEXMARK I-DEAS