

設計驗證
工程課
2026 -01- 13
發行
鈺齊科技開發股份有限公司

WAI GHA INDUSTRIAL CO., LTD.
APPROVAL SHEET

Customer	鈺緯科技	FILE NO.	WG240724001
Material	3M-7818	DATE	2026.01.08
Part No.	**3MDL4XLB760**(M2120)	Name	

CONSTRUCTION:

- Face-stock: 3.3 mil (82.5micron) matte silver polyester.
- Adhesive: 0.8 mil (20micron) #310 “Hi-Precision” acrylic. 180 degrees peel, 12”/min. 1” wide sample
  Stainless steel: 48 oz/inch (for 10-min. dwell).
  ABS: 48 oz/inch (for 10-min. dwell).
  Polypropylene: 8 oz/inch (for 10-min. dwell).
- Release Liner: 3.2 Mil (80 micron) 55# densified kraft. 180 degrees liner removal from face-stock, 90”/min. 1” wide sample.
  Typical value: 14 oz/inch (for 10-min. dwell)
- Temperature Resistance: Operating range is -40 degrees C to 150 degrees C; Application range is 50 degrees to 100 degrees C.
- Water Resistance: No change after three days at room temperature.
- Humidity Resistance: No change after three days at 32 degrees C and 90% relative humidity.
- Auto Oil Immersion: No change noted after four hours at room temperature.
- Acid/base Immersion: No change after four hours at room temperature in solutions of pH of 4 and pH of 10.
- Isopropyl Alcohol Immersion: No change after four hours at room temperature.
- Shelf Life: One year if properly stored at 22 degrees C and 50% relative humidity.

NOTE:

- Die-cutting single label size is 45mm(W) * 150 mm(L)
- The quantity of one roll is 500 pcs.
- P/N: **3MDL4XLB760**
- 需有自動裁切線，短邊出紙，一捲 500 張

SAMPLE: 如附件



DIVA APPROVED BY	DIVA CHECKED BY	WAI GHA CONFIRM BY	WAI GHA LISTING BY
設計驗證 工程課 2026 -01- 13 發行 鈺齊科技開發股份有限公司		張哲溫	蔣仲原 台北縣汐止市大同路三段194號1F 威嘉實業有限公司 TEL:8647-3525(代表號)