# Printing Materials - Component

**COMPANY**

WAI GHA INDUSTRIAL CO LTD
1ST FL
194 TA TUNG RD, SEC 3
HSI CHIH, 221 Taiwan

MH25635

| Model No. | Application Surface | Min Temp (°C) | Max Temp (°C) | Indoor Use | Outdoor Use | Additional Conditions |
|---|---|---|---|---|---|---|
| **Pressure-sensitive systems:** | | | | | | |
| Unprinted stock dsg: **WG-72826-MS**<br>**click for suitable additional printing inks** | Acrylic paint | -40 | 150 | X | X | O |
| | Alkyd paint | -40 | 150 | X | X | O |
| | Aluminum | -40 | 150 | X | X | O |
| | Epoxy paint | -40 | 150 | X | X | O |
| | Galvanized steel | -40 | 150 | X | X | O |
| | Polyester paint | -40 | 150 | X | X | O |
| | Porcelain | -40 | 150 | X | X | O |
| | Stainless steel | -40 | 150 | X | X | O |
| | Melamine | -40 | 100 | X | X | O |
| | Nylon - Polyamide | -40 | 100 | X | X | O, G |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | - | O |
| | Unsaturated polyester - thermoset | -40 | 100 | X | - | O |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | X | O |
| | Polycarbonate | -40 | 80 | X | X | O |
| | Polyphenylene oxide/ether | -40 | 80 | X | - | O |
| | Polystyrene | -40 | 80 | X | X | O |
| | Alkyd painted plastic | -40 | 60 | X | - | O |
| | Polyethylene | - | 60 | X | - | O |

| | | | | | | |
|---|---|---|---|---|---|---|
| Unprinted stock dsg: **WG-7815-MW**<br>**click for suitable additional printing inks** | Acrylic paint | -40 | 150 | X | X | - |
| | Alkyd paint | -40 | 150 | X | X | - |
| | Aluminum | -40 | 150 | X | X | - |
| | Epoxy paint | -40 | 150 | X | X | - |
| | Galvanized steel | -40 | 150 | X | X | - |
| | Polyester paint | -40 | 150 | X | X | - |
| | Polyethylene terephthalate | -40 | 150 | X | X | - |
| | Porcelain | -40 | 150 | X | X | - |
| | Stainless steel | -40 | 150 | X | X | - |
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | X | - |
| | Polybutylene terephthalate | -40 | 100 | X | X | - |
| | Polycarbonate | -40 | 100 | X | X | - |
| | Polyphenylene sulfide | -40 | 100 | X | - | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | X | - |
| | Polyphenylene oxide/ether | -40 | 80 | X | X | - |
| | Polypropylene | - | 80 | X | - | - |
| | Polystyrene | -40 | 80 | X | X | - |
| Printed label dsg: **WG-7816-7878**<br>**click for suitable additional printing inks** | Acrylic paint | -40 | 100 | X | X | - |
| | Alkyd paint | -40 | 100 | X | X | - |
| | Aluminum | -40 | 100 | X | X | - |
| | Epoxy paint | -40 | 100 | X | X | - |
| | Galvanized steel | -40 | 100 | X | X | - |
| | Glass | -40 | 100 | X | X | - |
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | X | - |
| | Polybutylene terephthalate | -40 | 100 | X | X | - |
| | Polycarbonate | -40 | 100 | X | X | - |
| | Polyester paint | -40 | 100 | X | X | - |
| | Polyethylene terephthalate | -40 | 100 | X | X | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Polyvinyl fluoride | -40 | 100 | X | X | - |
| | Polyvinylidene fluoride | -40 | 100 | X | X | - |
| | Porcelain | -40 | 100 | X | X | - |
| | Stainless steel | -40 | 100 | X | X | - |
| | Polyphenylene oxide/ether | -40 | 80 | X | X | - |
| | Polypropylene | -23 | 80 | X | X | - |
| | Polystyrene | -40 | 80 | X | X | - |
| | Acrylonitrile butadiene styrene | -40 | 60 | X | X | - |
| Printed label dsg: **WG-7816-BW click for suitable additional printing inks** | Acrylic paint | -40 | 150 | X | X | - |
| | Alkyd paint | -40 | 150 | X | X | - |
| | Aluminum | -40 | 150 | X | X | - |
| | Epoxy paint | -40 | 150 | X | X | - |
| | Galvanized steel | -40 | 150 | X | X | - |
| | Polyester paint | -40 | 150 | X | X | - |
| | Polyethylene terephthalate | -40 | 150 | X | X | - |
| | Porcelain | -40 | 150 | X | X | - |
| | Stainless steel | -40 | 150 | X | X | - |
| | Glass | -40 | 100 | X | X | - |
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | X | - |
| | Polybutylene terephthalate | -40 | 100 | X | X | - |
| | Polycarbonate | -40 | 100 | X | X | - |
| | Polyvinyl fluoride | -40 | 100 | X | X | - |
| | Polyvinylidene fluoride | -40 | 100 | X | X | - |
| | Polyphenylene oxide/ether | -40 | 80 | X | X | - |
| | Polypropylene | -23 | 80 | X | X | - |
| | Polystyrene | -40 | 80 | X | X | - |
| | Acrylonitrile butadiene styrene | -40 | 60 | X | X | - |
| Printed label dsg: **WG-7816-XX click for suitable additional printing inks** | Acrylic paint | -40 | 60 | X | X | - |
| | Acrylonitrile butadiene styrene | -40 | 60 | X | X | - |
| | Alkyd paint | -40 | 60 | X | X | - |
| | Aluminum | -40 | 60 | X | X | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Epoxy paint | -40 | 60 | X | X | - |
| | Galvanized steel | -40 | 60 | X | X | - |
| | Nylon - Polyamide | -40 | 60 | X | X | - |
| | Phenolic - Phenol Formaldehyde | -40 | 60 | X | X | - |
| | Polybutylene terephthalate | -40 | 60 | X | X | - |
| | Polycarbonate | -40 | 60 | X | X | - |
| | Polyester paint | -40 | 60 | X | X | - |
| | Polyethylene terephthalate | -40 | 60 | X | X | - |
| | Polyphenylene oxide/ether | -40 | 60 | X | X | - |
| | Polypropylene | - | 60 | X | - | - |
| | Polystyrene | -40 | 60 | X | X | - |
| | Porcelain | -40 | 60 | X | X | - |
| | Stainless steel | -40 | 60 | X | X | - |
| Unprinted stock dsg: **WG-7818-7744B**<br>Printed label dsg: **WG-7818-7744 click for suitable additional printing inks** | Aluminum | -40 | 125 | X | X | - |
| | Galvanized steel | -40 | 125 | X | X | - |
| | Polyethylene terephthalate | -40 | 125 | X | X | - |
| | Stainless steel | -40 | 125 | X | X | O |
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Polycarbonate | -40 | 100 | X | X | - |
| | Polyester paint | -40 | 100 | X | X | O |
| Printed label dsg: **WG-7818-MS click for suitable additional printing inks** | Acrylic paint | - | 150 | X | - | - |
| | Alkyd paint | - | 150 | X | - | - |
| | Aluminum | - | 150 | X | - | - |
| | Epoxy paint | - | 150 | X | - | - |
| | Galvanized steel | - | 150 | X | - | - |
| | Polyester paint | - | 150 | X | - | - |
| | Polyethylene terephthalate | -40 | 150 | X | X | - |
| | Porcelain | - | 150 | X | - | - |
| | Stainless steel | - | 150 | X | - | - |
| | Glass | -40 | 100 | X | X | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Phenolic - Phenol Formaldehyde | - | 100 | X | - | - |
| | Polybutylene terephthalate | - | 100 | X | - | - |
| | Polycarbonate | - | 100 | X | - | - |
| | Polyvinyl fluoride | -40 | 100 | X | X | - |
| | Polyvinylidene fluoride | -40 | 100 | X | X | - |
| | Polyphenylene oxide/ether | - | 80 | X | - | - |
| | Polypropylene | -23 | 80 | X | X | - |
| | Polystyrene | - | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | - | 60 | X | - | - |
| **Pressure-sensitive systems: Description - printed or unprinted matte silver polyester (PET) facestock with adhesive which is protected by a release liner** | | | | | | |
| Unprinted stock dsg: **WG-7818U-MSC**<br>Printed label dsg: **WG-7818P-MSC click for suitable additional printing inks** | Aluminum | -40 | 150 | X | X | - |
| | Galvanized steel | -40 | 150 | X | X | - |
| | Polyester paint | -40 | 150 | X | X | O |
| | Polyester powder paint | -40 | 150 | X | X | O |
| | Polyethylene terephthalate | -40 | 150 | X | X | - |
| | Stainless steel | -40 | 150 | X | X | O |
| | Liquid crystal polymer | -45 | 100 | X | X | - |
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Polycarbonate | -40 | 100 | X | X | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | X | - |
| **Pressure-sensitive systems: Description - printed white polyester facestock with adhesive which is protected by a release liner** | | | | | | |
| Printed label dsg: **WG-7871-BP click for suitable additional printing inks** | Acrylic paint | -40 | 150 | X | X | - |
| | Acrylic powder paint | -40 | 150 | X | X | - |
| | Alkyd paint | -40 | 150 | X | X | - |
| | Aluminum | -40 | 150 | X | X | - |
| | Epoxy paint | -40 | 150 | X | X | - |
| | Epoxy powder paint | -40 | 150 | X | X | - |
| | Galvanized steel | -40 | 150 | X | X | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Polyester paint | -40 | 150 | X | X | - |
| | Polyester powder paint | -40 | 150 | X | X | - |
| | Polyethylene terephthalate | -40 | 150 | X | X | - |
| | Porcelain | -40 | 150 | X | X | - |
| | Stainless steel | -40 | 150 | X | X | - |
| | Urethane powder paint | -40 | 150 | X | X | - |
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | X | - |
| | Polycarbonate | - | 100 | X | - | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | X | - |
| | PTFE coated metal | - | 80 | X | - | - |
| | Polyphenylene oxide/ether | -40 | 80 | X | X | - |
| | Polypropylene | - | 80 | X | - | - |
| | Polystyrene | -40 | 80 | X | X | - |
| | Polyvinyl chloride | -40 | 80 | X | - | - |
| | Zinc plated metal with chromate | -40 | 80 | X | X | - |
| **Pressure-sensitive systems:** | | | | | | |
| Unprinted stock dsg: **WG-7871-BW click for suitable additional printing inks** | Acrylic paint | -40 | 150 | X | X | - |
| | Acrylic powder paint | -40 | 150 | X | X | - |
| | Alkyd paint | -40 | 150 | X | X | - |
| | Aluminum | -40 | 150 | X | X | - |
| | Epoxy paint | -40 | 150 | X | X | - |
| | Epoxy powder paint | -40 | 150 | X | X | - |
| | Galvanized steel | -40 | 150 | X | X | - |
| | Polyester paint | -40 | 150 | X | X | - |
| | Polyester powder paint | -40 | 150 | X | X | - |
| | Polyethylene terephthalate | -40 | 150 | X | X | - |
| | Porcelain | -40 | 150 | X | X | - |
| | Stainless steel | -40 | 150 | X | X | - |
| | Urethane powder paint | -40 | 150 | X | X | - |
| | Nylon - Polyamide | -40 | 100 | X | X | - |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | X | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Polycarbonate | - | 100 | X | - | - |
| | PTFE coated metal | - | 80 | X | - | - |
| | Polyphenylene oxide/ether | -40 | 80 | X | X | - |
| | Polypropylene | - | 80 | X | - | - |
| | Polystyrene | -40 | 80 | X | X | - |
| | Zinc plated metal with chromate | -40 | 80 | X | X | - |
| | Acrylonitrile butadiene styrene | -40 | 60 | X | X | - |
| | Polyvinyl chloride | -40 | 60 | X | - | - |
| Unprinted stock dsg: **WG-7875-MP**<br>**click for suitable additional printing inks** | Acrylic paint | - | 150 | X | - | - |
| | Alkyd paint | - | 150 | X | - | - |
| | Aluminum | - | 150 | X | - | - |
| | Epoxy paint | - | 150 | X | - | - |
| | Galvanized steel | - | 150 | X | - | - |
| | Polyester paint | - | 150 | X | - | - |
| | Porcelain | - | 150 | X | - | - |
| | Stainless steel | - | 150 | X | - | - |
| | Nylon - Polyamide | - | 100 | X | - | - |
| | Phenolic - Phenol Formaldehyde | - | 100 | X | - | - |
| | Polybutylene terephthalate | - | 100 | X | - | - |
| | Polycarbonate | - | 100 | X | - | - |
| | Polyphenylene oxide/ether | - | 80 | X | - | - |
| | Polypropylene | - | 80 | X | - | - |
| | Polystyrene | - | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | - | 60 | X | - | - |
| **Pressure-sensitive systems: Description - unprinted white polyester (PET) facestock with adhesive which is protected by a release liner** | | | | | | |
| Unprinted stock dsg: **WG-B483A-BW**<br>**click for suitable additional printing inks** | Acrylic powder paint | -40 | 80 | X | X | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | X | - |
| | Alkyd paint | -40 | 80 | X | X | - |
| | Aluminum | -40 | 80 | X | X | - |
| | Epoxy powder paint | -40 | 80 | X | X | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Galvanized steel | -40 | 80 | X | X | - |
| | Polycarbonate | -40 | 80 | X | X | - |
| | Polyester powder paint | -40 | 80 | X | X | - |
| | Polyphenylene oxide/ether | -40 | 80 | X | X | - |
| | Polypropylene | -40 | 80 | X | X | - |
| | Polyurethane powder paint | -40 | 80 | X | X | - |
| | Stainless steel | -40 | 80 | X | X | - |
| **Pressure-sensitive systems:** | | | | | | |
| Printed label dsg: **WG-BH-0-#9H click for suitable additional printing inks** | Aluminum | -40 | 100 | X | - | - |
| | Galvanized steel | -40 | 100 | X | - | - |
| | Stainless steel | -40 | 100 | X | - | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | - | - |
| | Nylon - Polyamide | -40 | 80 | X | - | - |
| | Polycarbonate | -40 | 80 | X | - | - |
| Printed label dsg: **WG-BH-0-7533 click for suitable additional printing inks** | Aluminum | -40 | 100 | X | - | - |
| | Galvanized steel | -40 | 100 | X | - | - |
| | Stainless steel | -40 | 100 | X | - | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | - | - |
| | Nylon - Polyamide | -40 | 80 | X | - | - |
| | Polycarbonate | -40 | 80 | X | - | - |
| Printed label dsg: **WG-BH-2-#9H click for suitable additional printing inks** | Aluminum | -40 | 100 | X | - | - |
| | Galvanized steel | -40 | 100 | X | - | - |
| | Stainless steel | -40 | 100 | X | - | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | - | - |
| | Nylon - Polyamide | -40 | 80 | X | - | - |
| | Polycarbonate | -40 | 80 | X | - | - |
| Printed label dsg: **WG-BH-2-7533 click for suitable additional printing inks** | Aluminum | -40 | 100 | X | - | - |
| | Galvanized steel | -40 | 100 | X | - | - |
| | Stainless steel | -40 | 100 | X | - | - |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | - | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Nylon - Polyamide | -40 | 80 | X | - | - |
| | Polycarbonate | -40 | 80 | X | - | - |
| **Pressure-sensitive systems: Description - unprinted matte black polycarbonate facestock with adhesive which is protected by a release liner** | | | | | | |
| Unprinted stock dsg: **WG-FR700-7533**<br>**click for suitable additional printing inks** | Aluminum | -23 | 80 | X | X | - |
| | Magnesium | -23 | 80 | X | X | - |
| | Polycarbonate | -23 | 80 | X | X | - |
| **Pressure-sensitive systems: Description - unprinted white polyester (PET) facestock with adhesive which is protected by a release liner** | | | | | | |
| Unprinted stock dsg: **WG-HTLW50J-BW**<br>**click for suitable additional printing inks** | Acrylic paint | -20 | 100 | X | - | - |
| | Epoxy paint | -20 | 100 | X | - | - |
| | Galvanized steel | -20 | 100 | X | - | - |
| | Polycarbonate | -20 | 100 | X | - | - |
| | Polyester paint | -20 | 100 | X | - | - |
| | Polyphenylene oxide/ether | -20 | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | -20 | 60 | X | - | - |
| **Pressure-sensitive systems: Description - overprint coated printed white polyester (PET) facestock with adhesive which is protected by a release liner** | | | | | | |
| Printed label dsg: **WG-HTLW50J-MI**<br>**click for suitable additional printing inks** | Acrylic paint | -20 | 100 | X | - | - |
| | Epoxy paint | -20 | 100 | X | - | - |
| | Galvanized steel | -20 | 100 | X | - | - |
| | Polycarbonate | -20 | 100 | X | - | - |
| | Polyester paint | -20 | 100 | X | - | - |
| | Polyphenylene oxide/ether | -20 | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | -20 | 60 | X | - | - |
| **Pressure-sensitive systems: Description - overlaminated printed white polyester (PET) facestock with adhesive which is protected by a release liner** | | | | | | |
| Printed label dsg: **WG-HTLW50J-MS**<br>**click for suitable additional printing inks** | Acrylic paint | -20 | 100 | X | - | - |
| | Epoxy paint | -20 | 100 | X | - | - |
| | Galvanized steel | -20 | 100 | X | - | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Polycarbonate | -20 | 100 | X | - | - |
| | Polyester paint | -20 | 100 | X | - | - |
| | Polyphenylene oxide/ether | -20 | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | -20 | 60 | X | - | - |
| **Pressure-sensitive systems:** | | | | | | |
| Printed label dsg: **WG-K56025-MS, WG-K56275-MS click for suitable additional printing inks** | Acrylic paint | -40 | 150 | X | X | O |
| | Aluminum | -40 | 150 | X | X | O |
| | Epoxy paint | -40 | 150 | X | X | O |
| | Galvanized steel | -40 | 150 | X | X | O |
| | Porcelain | -40 | 150 | X | X | O |
| | Stainless steel | -40 | 150 | X | X | O |
| | Alkyd paint | -40 | 100 | X | X | O |
| | Melamine | -40 | 100 | X | - | O |
| | Nylon - Polyamide | -40 | 100 | X | - | O |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | - | O |
| | Polyester paint | -40 | 100 | X | X | O |
| | Unsaturated polyester - thermoset | -40 | 100 | X | - | O |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | - | O |
| | Polycarbonate | -40 | 80 | X | X | O |
| | Polyphenylene oxide/ether | -40 | 80 | X | - | O |
| | Polypropylene | -40 | 80 | X | - | O |
| | Polystyrene | -40 | 80 | X | - | O |
| | Alkyd painted plastic | -40 | 60 | X | - | O |
| | Polyethylene | - | 60 | X | - | O |
| Printed label dsg: **WG-K56250-MS click for suitable additional printing inks** | Acrylic paint | -40 | 150 | X | X | O |
| | Aluminum | -40 | 150 | X | X | O |
| | Epoxy paint | -40 | 150 | X | X | O |
| | Galvanized steel | -40 | 150 | X | X | O |
| | Porcelain | -40 | 150 | X | X | O |
| | Stainless steel | -40 | 150 | X | X | O |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Alkyd paint | -40 | 100 | X | X | O |
| | Melamine | -40 | 100 | X | - | O |
| | Nylon - Polyamide | -40 | 100 | X | X | O |
| | Phenolic - Phenol Formaldehyde | -40 | 100 | X | - | O |
| | Polyester paint | -40 | 100 | X | X | O |
| | Unsaturated polyester - thermoset | -40 | 100 | X | - | O |
| | Acrylonitrile butadiene styrene | -40 | 80 | X | - | O |
| | Polycarbonate | -40 | 80 | X | X | O |
| | Polyphenylene oxide/ether | -40 | 80 | X | - | O |
| | Polypropylene | -40 | 80 | X | - | O |
| | Polystyrene | -40 | 80 | X | - | O |
| | Alkyd painted plastic | -40 | 60 | X | - | O |
| | Polyethylene | - | 60 | X | - | O |
| Printed label dsg: **WG-MZ0052-MS click for suitable additional printing inks** | Acrylic paint | -20 | 100 | X | - | - |
| | Epoxy paint | -20 | 100 | X | - | - |
| | Galvanized steel | -20 | 100 | X | - | - |
| | Polycarbonate | -20 | 100 | X | - | - |
| | Polyester paint | -20 | 100 | X | - | - |
| | Polyphenylene oxide/ether | -20 | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | -20 | 60 | X | - | - |
| Printed label dsg: **WG-PO3B-MS, WG-PO6B-MS, WG-PO9B-MS click for suitable additional printing inks** | Alkyd paint | -23 | 125 | X | - | - |
| | Aluminum | -23 | 125 | X | - | - |
| | Stainless steel | -23 | 125 | X | - | - |
| | Acrylonitrile butadiene styrene | -23 | 60 | X | - | - |
| | Polystyrene | -23 | 60 | X | - | - |
| Printed label dsg: **WG-POB7-BW click for suitable additional printing inks** | Aluminum | -20 | 150 | X | - | - |
| | Bare steel | -20 | 150 | X | - | - |
| | Epoxy paint | -20 | 150 | X | - | - |

| | | | | | | |
|---|---|---|---|---|---|---|
| Printed label dsg: **WG-POB7H-BW click for suitable additional printing inks** | Aluminum | -20 | 150 | X | - | - |
| | Epoxy paint | -20 | 150 | X | - | - |
| | Polyester paint | -20 | 150 | X | - | - |
| | Stainless steel | -20 | 150 | X | - | - |
| | Polycarbonate | -20 | 100 | X | - | - |
| | Polystyrene | -20 | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | -20 | 60 | X | - | - |
| | Acrylonitrile butadiene styrene/Polycarbonate | -20 | 60 | X | - | - |
| | Polyethylene | -5 | 60 | X | - | - |
| Printed label dsg: **WG-SY15-PP click for suitable additional printing inks** | Alkyd paint | -23 | 100 | X | - | - |
| | Aluminum | -23 | 100 | X | - | - |
| | Stainless steel | -23 | 100 | X | - | - |
| | Acrylonitrile butadiene styrene | -23 | 60 | X | - | - |
| | Polystyrene | -23 | 60 | X | - | - |
| Printed label dsg: **WG-T-HTLW50(EB)-MS click for suitable additional printing inks** | Epoxy paint | -20 | 100 | X | - | - |
| | Galvanized steel | -20 | 100 | X | - | - |
| | Polycarbonate | -20 | 100 | X | - | - |
| | Polyester paint | -20 | 100 | X | - | - |
| | Acrylic paint | -20 | 80 | X | - | - |
| | Polyphenylene oxide/ether | -20 | 80 | X | - | - |
| | Acrylonitrile butadiene styrene | -20 | 60 | X | - | - |

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

G - Occasional exposure to Gasoline splashing.

O - Occasional exposure to Lubricating Oil.

Marking: Company name and model designation and the Recognized Component Mark, .

Last Updated on 2023-12-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."