

NOTES:

1. 100% OPEN & SHORTS AND MISS WIRE TEST.
   a. CONDUCTIVE RESISTANCE:5 OHM MAX.
   b. INSULATION RESISTANCE:5M OHM MIN.
   c. HI-POT:DC300V/0.01S.
2. ALL MATERIALS SHALL COMPLY WITH RoHS.

WIRING DIAGRAM

P1	COLOR	P2
1	Red	2
2	White	5
3	Green	4
4	Black	3
Shell	Braid	1

包裝方式:
每50PCS用PE膠膜綁成一把

PART	MPN	DESCRIPTION	QTY
⑧	S04B000451	Heat shink tube:Φ4.0*20mm,color:black	1 PCS
⑦	S04B000459	Heat shink tube:Φ0.6*20mm,color:black	1 PCS
⑥	P02B50P002	Outer mold:50p PVC color:black	4 G
⑤	P01W00P001	Inner molded:transparent LDPE	2 G
④	L13300W077	Terminal:PH2.0-T(WT200F0-T004),tin plated	5 PCS
③	L12005W213	Housing:PH2.0-05P(WT200F0-05H),color:white	1 PCS
②	L01204W010	USB A/M:soldering type,shell:nickel plated,insulation:white,contact:G/F(三件式)	1 SET
①	CRB4401014	Cable:UL2725 28AWG*1P+24AWG*2C+AB,OD:4.0mm,jacket:black PVC(LC-130-256)	480 MM

CABLE MARKING:
USB SHIELDED HIGH SPEED CABLE 2.0 REVISION E343712 AWM 2725 28AWG/1PR AND 24AWG/2C 80℃ 30V VW-1 DHE

理義科技股份有限公司 LIYITEC INCORPORATED	料號	4140-400A-96053	品名	USB CONTROLLER CABLE			日期	2026.02.04	製圖員	Ver.: A PAGE OF